

Champion Snatch Blocks

- Hooks and side plates are forged alloy steel and heat treated.
- Shackles and yokes are forged and heat treated steel.
- All parts are forged.
- Side plates are designed to eliminate possibility of rope jamming.
- Can be furnished with bronze bushings or sealed roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- Hook and shackle assemblies can be interchanged.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.
- All sizes are RFID Equipped.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26



Sheave Diameter (in.)	Bearing Code	Stock No.			Wire Rope Size (in.)	Working Load Limit (t)	Weight Each (lbs.)		
		420 with Hook	421 with Shackle	406 Tail Board			420 with Hook	421 with Shackle	406 Tail Board
6	BB	169374	169481	167973	3/4 - 7/8	12	40	48	24
6	RB	169392	204120	167982	3/4 - 7/8	12	40	48	24
8	BB	169418	169515	167991	3/4 - 7/8	15	51	57	30
8	RB	169445	204193	168008	3/4 - 7/8	15	51	57	30
10	BB	110221	110720	103186	3/4 - 7/8	15	63	69	42
10	RB	110258	110757	103202	3/4 - 7/8	15	63	69	42

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size.
 NOTE: Tail Board does not contain the spool that is required with the hook (420) and shackle (421) snatch blocks

BLOCKS & SHEAVES