

Campbell®

System 3, Proof Coil Chain (Grade 30)

- Uses: Excellent general-purpose chain of standard commercial quality
- Frequently used for fabricating tow chains, binding or tie down chains and logging chains
- Standard Material: Low carbon steel
- Standard Finish: Self Colored (S.C.) or Galvanized (GALV); also available Zinc Plated (Z.P.) 3/16" through 1/2"; and polycoated
- Hallmarking: "C3" or "M3" on 5/16" (8mm) and larger
- Proof tested
- Packaging: Drums and half drums (order unit is "feet"), pails and refill reels to fit Campbell merchandisers (order unit is "each")
- **Do not use for overhead lifting**



Trade Size	Mat. Dia.	Inside Dimensions			Self Colored		Zinc Plated		Galvanized		Working Load Limit	Length/ft. per drum	Lb/100'	Links/ft.
		Length	Width		Cat. No.	UPC No. 020418	Cat. No.	UPC No. 020418	Cat. No.	UPC No. 020418				
1/8	4 .16	4 .89	23 .29	7	0120202	056932	--	--	0120232	056949	400 180	1000	19	13.5
3/16	6 .21	6 .95	24 .34	9	0120302	056970	0120322	057007	0120332	057045	800 365	1000	35	12.6
1/4	7 .26	7 1.20	30 .45	11	0120402	057076	0120422	057106	0120432	057144	1300 580	800	56	10.0
5/16	8 .31	8 1.27	32 .47	12	0120502	057205	0120522	057243	0120532	057281	1900 860	550	83	9.4
3/8	10 .37	10 1.36	35 .57	14	0120602	057335	0120622	057373	0120632	057410	2650 1200	400	125	8.8
7/16	12 .47	12 1.37	35 .75	19	--	--	--	--	0120732	057489	3700 1680	300	210	8.8
1/2	13 .48	13 1.70	43 .75	19	0120802	057502	0120822	057526	0120832	057557	4500 2030	200	238	7.1
5/8	16 .66	17 2.10	53 .87	22	0121002	057595	--	--	0121032	057618	6900 3130	150	390	5.7
3/4	20 .78	20 2.70	69 1.02	26	0121202	057632	--	--	0121232	057656	10,600 4800	100	536	4.4

System 4, High Test Chain (Grade 43)

- Uses: Designed for use in load binding, towing, logging and other applications requiring high strength
- Standard Material: Carbon steel
- Standard Finish: Bright (BRT) and Galvanized(GALV); Zinc Plated (Z.P.) available in drums, pails and reels
- Hallmarking: "C4" or "M4"
- Proof tested
- Packaging: Drums (order unit is "feet"), pails and refill reels to fit Campbell merchandisers (order unit is "each")
- **Do not use for overhead lifting**



Trade Size	Mat. Dia.	Inside Dimensions			Bright Cat. No.	UPC No. 020418	Zinc Plated		Galvanized		Working Load Limit	Feet/Drum	Lb/100'	Links/ft.
		Length	Width				Cat. No.	UPC No. 020418	Cat. No.	UPC No. 020418				
1/4	7 .28	7 1.20	30 .45	11	0180412	058769	0180422	058790	0180432	058820	2600 1180	800	63	10.0
5/16	8 .33	8 1.27	32 .47	12	0180512	058851	0180522	058882	0180532	058912	3900 1770	550	95	9.4
3/8	10 .39	10 1.15	29 .58	15	0180612	058943	--	--	0180632	059018	5400 2450	400	155	10.4
1/2	13 .53	13 1.70	43 .75	19	0180812	059094	--	--	0180832	059155	9200 4170	200	260	7.1
5/8	16 .66	17 1.94	49 .93	24	0181012	059186	--	--	0181032	059216	13,000 5910	150	356	6.2
3/4	20 .78	20 2.21	56 1.10	28	0181212	059254	--	--	--	--	20,200 9180	100	581	5.4

System 7, Transport Chain (Grade 70)

- Uses: For use in load binding, towing and logging
- Can be used in accordance with Department of Transportation regulations
- Standard Material: Heat treated carbon steel
- Standard Finish: Zinc electroplate with yellow chromate conversion coating
- Hallmarking: "C7" or "M7"
- Proof tested
- Packaging: Drums and half drums (order unit is "feet"), pails (order unit is "each")
- **Do not use for overhead lifting**



Trade Size	Mat. Dia.	Inside Dimensions			Cat. No.	UPC No. 020418	Working Load Limit		Feet/Drum	Lb/100'	Links/ft.
		Length	Width				lb	kg			
1/4	7 .31	8 .94	24 .46	12	0510412	063763	3150 1430	800	94	12.8	
5/16	8 .34	9 1.01	26 .48	12	0510512	063800	4700 2130	550	111	11.9	
3/8	10 .41	10 1.36	35 .57	14	0510612	063848	6600 2990	400	150	8.8	
7/16	12 .47	12 1.29	33 .67	17	0510712	063886	8750 3970	300	212	9.3	
1/2	13 .53	13 1.70	43 .75	19	0510812	063916	11,300 5130	200	260	7.1	