

TRIANGLE - CHOKER TCA/TCS – Type 1 TRIANGLE - TRIANGLE TTA/TTS – Type 2



TCA Type 1 - Aluminum Choker & Basket Fitting



TTA Type 2 - Aluminum Basket Fittings



TCS Type 1 - Steel Choker & Basket Fitting



TTS Type 2 - Steel Basket Fittings

These are nylon or polyester web slings with steel or aluminum end fittings for use in vertical, choker and basket hitch applications.







These are nylon or polyester web slings with steel triangles, aluminum triangles, links or shackles for use in vertical or basket hitch applications.

Features:

These are nylon or polyester web slings with steel or aluminum end fittings for use in vertical, choker and basket hitch applications.

How to Order:

* Insert TCA/TTA prefix for aluminum fitting or TCS/TTS prefix for steel fitting.

Stock No.	Width (inches)	Ply	Rated Capacities in Lbs.					
			Vertical 	Choker** 	Basket 	60° 	45° 	30° 
*-1-902	2	1	3,100	2,480	6,200	5,369	4,383	3,100
*-2-902	2	2	6,200	4,960	12,400	10,738	8,767	6,200
*-1-903	3	1	4,700	3,760	9,400	8,140	6,646	4,700
*-2-903	3	2	8,800	7,040	17,600	15,242	12,443	8,800
*-1-904	4	1	6,200	4,960	12,400	10,738	8,767	6,200
*-2-904	4	2	11,000	8,800	22,000	19,052	15,554	11,000
*-1-906	6	1	9,300	7,440	18,600	16,108	13,150	9,300
*-2-906	6	2	16,500	13,200	33,000	28,578	23,331	16,500
*-1-908	8	1	11,800	9,440	23,600	20,438	16,665	11,800
*-2-908	8	2	22,700	18,160	45,400	39,316	32,098	22,700
*-1-910	10	1	14,700	11,760	29,400	25,460	20,786	14,700
*-2-910	10	2	28,400	22,720	56,800	49,189	40,158	28,400
*-1-912	12	1	17,600	14,080	35,200	30,483	24,886	17,600
*-2-912	12	2	34,100	27,280	68,200	59,061	48,217	34,100

** Choker rated capacities apply to Type 1 slings only.

Notes:

- Polyester Webbing standard, unless otherwise requested
- Steel fittings are standard on both 1-ply and 2-ply slings.
- These slings are also available in 3-ply and 4-ply construction
- Aluminum fittings are available up to 6" in 1-ply capacities.
- See the next page for rated capacities of hardware.

Warning: Never use aluminum fittings where fumes, vapors, mists or liquids of caustics are present. Horizontal sling angles less than 30° shall not be used.