

EYE & EYE - FLAT EEF – Type 3

EYE & EYE - TWIST EET – Type 4

E/E Type 3 – These are web slings with a flat loop eye on each end. The eye openings are in the same plane as sling. This sling can be used in all hitches (vertical, Choker, Basket).



E/E Type 4 – These are web slings with a twisted loop eye on each end. The eye openings are at a right angle to the sling body. This sling is suitable in all hitches, but recommended when the sling will be used primarily in a choker hitch application.

Stock No. <i>(* start with EEF or EET)</i>	Width (inches)	Ply	Rated Capacities in Pounds						Nominal Eye Dimensions	
					Basket Hitch				Eye Length L (inches)	Eye Width W (inches)
										
*-1-901	1	1	1,600	1,280	3,200	2,771	2,262	1,600	9	1
*-2-901	1	2	3,100	2,480	6,200	5,369	4,383	3,100	9	1
*-3-901	1	3	4,100	3,300	8,200	7,052	5,781	4,100	12	1
*-4-901	1	4	5,500	4,400	11,000	9,526	7,777	5,500	12	1
*-1-902	2	1	3,100	2,480	6,200	5,369	4,383	3,100	9	2
*-2-902	2	2	6,200	4,960	12,400	10,738	8,767	6,200	9	2
*-3-902	2	3	8,200	6,600	16,400	14,104	11,562	8,200	12	2
*-4-902	2	4	11,000	8,800	22,000	19,052	15,554	11,000	12	2
*-1-903	3	1	4,700	3,760	9,400	8,140	6,646	4,700	12	1-1/2
*-2-903	3	2	8,800	7,040	17,600	15,242	12,443	8,800	12	1-1/2
*-3-903	3	3	12,300	9,900	24,600	21,156	17,343	12,300	15	1-1/2
*-4-903	3	4	16,400	13,120	32,800	28,405	23,190	16,400	15	1-1/2
*-1-904	4	1	6,200	4,960	12,400	10,738	8,767	6,200	12	2
*-2-904	4	2	11,000	8,800	22,000	19,052	15,554	11,000	12	2
*-3-904	4	3	15,300	12,200	30,600	26,316	21,573	15,300	15	2
*-4-904	4	4	20,400	16,320	40,800	35,333	28,846	20,400	15	2
*-1-906	6	1	9,300	7,440	18,600	16,108	13,150	9,300	12	2
*-2-906	6	2	16,500	13,200	33,000	28,578	23,331	16,500	15	2
*-3-906	6	3	22,900	18,300	45,800	39,388	32,289	22,900	18	3
*-4-906	6	4	30,600	24,480	61,200	52,999	43,268	30,600	18	3
*-1-908	8	1	11,800	9,440	23,600	20,438	16,665	11,800	18	3
*-2-908	8	2	22,700	18,160	45,400	39,316	32,098	22,700	18	3
*-3-908	8	3	30,700	24,600	61,400	52,804	43,287	30,700	24	4
*-4-908	8	4	40,960	32,768	81,920	70,451	57,753	40,960	24	4
*-1-910	10	1	14,700	11,760	29,400	25,460	20,786	14,700	18	3-1/2
*-2-910	10	2	28,400	22,720	56,800	49,189	40,158	28,400	18	3-1/2
*-3-910	10	3	36,000	28,800	72,000	61,920	50,760	36,000	24	5
*-4-910	10	4	48,000	38,400	96,000	82,560	67,680	48,000	24	5
*-1-912	12	1	17,600	14,080	35,200	30,483	24,886	17,600	24	4
*-2-912	12	2	34,100	27,280	68,200	59,061	48,217	34,100	24	4
*-3-912	12	3	40,300	32,200	80,600	69,316	56,823	40,300	24	6
*-4-912	12	4	53,760	43,008	107,520	92,467	75,801	53,760	24	6

* Insert EEF prefix to indicate Type 3 and EET prefix to indicate Type 4.*

* Polyester Webbing standard, unless otherwise requested

Warning: Horizontal sling angles less than 30° shall not be used.

