

Nylon or polyester web sling designed in a continuous loop formed by joining the ends of webbing together with a load bearing splice. Sometimes referred to as a grommet. Can be used in any hitch.



Stock No.	Width (inches)	Ply	Rated Capacities in Pounds						Taper	
			Vertical	Choker	Basket Hitch				Width W (inches)	Length L (inches)
						60°	45°	30°		
EN-1-901	1	1	3,100	2,480	6,200	5,369	4,525	3,100	—	—
EN-2-901	1	2	6,200	4,960	12,400	10,738	8,767	6,200	—	—
EN-3-901	1	3	8,200	6,600	16,400	14,104	11,562	8,200	—	—
EN-4-901	1	4	11,000	8,800	22,000	19,052	15,554	11,000	—	—
EN-1-902	2	1	6,200	4,960	12,400	10,738	8,767	6,200	1	9
EN-2-902	2	2	12,400	9,920	24,800	21,477	17,534	12,400	1	9
EN-3-902	2	3	16,500	13,200	33,000	28,380	23,265	16,500	*	*
EN-4-902	2	4	22,000	17,600	44,000	38,104	31,108	22,000	—	—
EN-1-903	3	1	9,400	7,520	18,800	16,281	13,292	9,400	1-1/2	12
EN-2-903	3	2	17,600	14,080	35,200	30,483	24,866	17,600	1-1/2	12
EN-3-903	3	3	24,700	19,800	49,400	42,484	34,827	24,700	*	*
EN-4-903	3	4	32,900	26,320	65,800	56,983	46,521	32,900	—	—
EN-1-904	4	1	12,400	9,920	24,800	21,477	17,534	12,400	2	12
EN-2-904	4	2	22,000	17,600	44,000	38,104	31,108	22,000	2	12
EN-3-904	4	3	30,600	24,500	61,200	52,632	43,146	30,600	*	*
EN-4-904	4	4	40,800	32,640	81,600	70,666	57,691	40,800	—	—
EN-1-906	6	1	18,600	14,880	37,200	32,215	26,300	18,600	2	15
EN-2-906	6	2	33,000	26,400	66,000	57,156	46,662	33,000	3	15
EN-3-906	6	3	45,900	36,700	91,800	78,948	64,719	45,900	*	*
EN-4-906	6	4	61,200	48,960	122,400	105,998	86,537	61,200	—	—
EN-1-908	8	1	21,200	16,960	42,400	36,718	29,977	21,200	3	18
EN-2-908	8	2	42,300	33,840	84,600	73,264	59,812	42,300	4	18
EN-3-908	8	3	61,400	49,100	122,800	105,608	86,574	61,400	*	*
EN-4-908	8	4	81,920	65,536	163,840	140,902	115,507	81,920	—	—
EN-1-910	10	1	26,500	21,200	53,000	45,580	37,471	26,500	3-1/2	18
EN-2-910	10	2	52,900	42,320	105,800	91,623	74,801	52,900	5	18
EN-3-910	10	3	72,000	57,600	144,000	123,840	101,520	72,000	*	*
EN-4-910	10	4	96,000	76,800	192,000	165,120	135,360	96,000	—	—
EN-1-912	12	1	31,800	25,440	63,600	55,078	44,965	31,800	4	18
EN-2-912	12	2	63,500	50,800	127,000	109,982	89,789	63,500	6	18
EN-3-912	12	3	80,600	64,500	161,200	138,632	113,646	80,600	*	*
EN-4-912	12	4	107,520	86,016	215,040	184,934	151,603	107,520	—	—

Please specify when sling is to be tapered at hook contact area.

*Three-ply slings are tapered by special request only.

*Polyester Webbing standard, unless otherwise requested

Warning: Horizontal sling angles less than 30° shall not be used.