





## WIDE BODY BASKET WBB - TYPE 8

These are designed for use in basket hitches where you need a wide sling for load stability and for proper handling of fragile or highly finished surfaces. Eyes of slings are tapered to fit in hoist or crane hooks.



Stock No.	Width (inches)	Ply	Rated Capacity in Lbs.				Nominal Eye Dimensions	
							Eye Length L (inches)	Eye Width W (inches)
WBB-1-906	6	1	17,200	14,900	12,100	8,600	12	1-1/2
WBB-2-906	6	2	32,000	27,700	22,600	16,000	15	1-1/2
WBB-1-908	8	1	22,600	19,600	16,000	11,300	12	2
WBB-2-908	8	2	42,000	36,400	29,700	21,000	15	2
WBB-1-910	10	1	28,200	24,400	20,000	14,100	15	1-3/4
WBB-2-910	10	2	52,500	45,500	37,100	26,300	18	2-1/2
WBB-1-912	12	1	33,900	29,300	23,900	16,900	15	2
WBB-2-912	12	2	63,000	54,600	44,600	31,500	18	3*
WBB-1-916	16	1	43,900	38,000	31,000	22,000	18	3*
WBB-2-916	16	2	72,800	63,000	51,400	36,400	24	4*
WBB-1-920	20	1	51,000	44,100	36,000	25,500	24	3-1/2*
WBB-2-920	20	2	80,000	69,300	56,500	40,000	24	5*
WBB-1-924	24	1	56,400	48,900	39,900	28,200	24	4*
WBB-2-924	24	2	88,400	76,600	62,500	44,200	24	6*

\* Narrower taper available on special request only.

\* Wider widths available upon request.

\* Polyester Webbing standard, unless otherwise requested





Wear pads are available for eyes and sling body on request.

**Warning:** Horizontal sling angles less than 30° shall not be used.

## LOAD BALANCER BASKET LBB - TYPE 9



These are designed for applications where you need a wide sling for load stability and for proper handling of fragile or highly finished surfaces. They have lower rated capacity than the Wide Body Basket. Eyes are constructed to fit properly on small hoist hooks and are reinforced for longer life.

Stock No.	Width (inches)	Ply	Rated Capacity in Lbs.				Nominal Eye Dimensions	
							Eye Length L (inches)	Eye Width W (inches)
LBB-1-906	6	1	6,000	5,200	4,200	3,000	1	9
LBB-1-908	8	1	6,000	5,200	4,200	3,000	1	12
LBB-1-910	10	1	6,000	5,200	4,200	3,000	1	15
LBB-1-912	12	1	6,000	5,200	4,200	3,000	1	18
LBB-1-916	16	1	10,000	8,700	7,100	5,000	2	24
LBB-1-920	20	1	10,000	8,700	7,100	5,000	2	24
LBB-1-924	24	1	10,000	8,700	7,100	5,000	2	24

\* Wider widths available upon request.

\* Polyester Webbing standard, unless otherwise requested

**Warning:** Horizontal sling angles less than 30° shall not be used.

