
# FAST, ONE-HANDED SNUGDOWNS

Ideal for use on pallets, in trucks or vans, baggage compartments, shipping containers or aircraft. Just snug down your load with a Ratchet Snugger control binder, adjust the tension and lock in place by pressing down on the ratchet handle. Your load is secure. When unloading, you can release the Ratchet Snugger binder just as easily. Choose from 1,670-lb. to 3,300-lb. Working Load Limits (WLL) in 2" webbing. Also available in 1", 3" and 4" sizes.



(Ratchet Snugger Eye [Type RSEE] also available.)

Ratchet Snugger Straight Assemblies (Type RSA). One end of webbing is sewn to the ratchet head, leaving the other end free to pass around the load or through narrow openings to insert into the ratchet spool. Fabricated to any practical web length plus 6" extra length for end hold. Optional sliding sleeve-type wear pads, ratchet pads and corner protectors help protect the webbing on both types



of binders.

*Ratchet Snugger two-piece devices (Type RS\_\_).* All feature metal fittings or eyes sewn at the ends of two pieces of webbing with the shorter piece sewn to the ratchet head. The variable length piece is heat-sealed to prevent fraying for easy insertion into the ratchet spool. Fabricated to any practical web length (between bearing points of eyes or hooks) plus 6" extra length for end hold. Ratchet buckle and metal end fittings are plated to resist corrosion. Other fittings are also available.



## Flat Hooks

Type RSFF1802 Rated 3,300 lbs. WLL; 10,000 lbs. nominal strength Order code letter F (1 3/4" or 2" only).

#### **Snap Hooks**

Type RSSS1802 2" Snap Hook rated 3,300 lbs. WLL; 10,000 lbs. nominal strength Order code letter S.

#### Ratchets

Standard Handle Rated 3,300 lbs. WLL; 10,000 lbs. nominal strength

Long/Wide Handle Rated 3,300 lbs. WLL; 10,000 lbs. nominal strength

### **D-Rings**

Type RSDD1802 Rated 3,300 lbs. WLL; 10,000 lbs. nominal strength Order code letter D.

