

STEEL LINED CHOKER BELT MODEL: TPC



Model # TPC - Lined Steel Choker Belt

- Aligns pipe exactly without slippage for bending, welding, etc.
- Roll pipe, pull pipe, secure extreme bends-all without damage
- Fastest tool available for positioning and handling pipe
- Fully adjustable for coating thickness
- Super Heavy Duty Barrier webbing for increased life and gripping efficiency
- Easily repairable in field for longer life
- Used around the world on pipe up to 60"
- Replacement Parts Available



Part No.	Max Pipe Diameter		Belt Width		Approx. Weight		Rated Capacity	
	in.	mm.	in.	mm.	lbs.	kg	lbs.	kg.
TPC-110	10	254	8	203	50	23	7,600	3,447
TPC-112	12	305	8	203	93	42	7,600	3,447
TPC-114	14	356	8	203	109	49	7,600	3,447
TPC-116	16	406	8	203	115	52	7,600	3,447
TPC-118	18	457	8	203	120	54	7,600	3,447
TPC-120	20	508	8	203	125	57	7,600	3,447
TPC-124	24	607	8	203	133	60	16,800	7,620
TPC-126	26	660	8	203	137	62	16,800	7,620
TPC-128	28	711	8	203	140	64	16,800	7,620
TPC-130	30	762	8	203	142	64	16,800	7,620
TPC-136	36	660	8	203	160	73	16,800	7,620
TPC-140	40	1016	8	203	190	86	21,400	9,707
TPC-142	42	1067	8	203	200	91	21,400	9,707
TPC-148	48	1219	8	203	210	95	21,400	9,707
TPC-156	56	1422	8	203	225	102	27,200	12,338
TPC-160	60	1524	8	203	235	107	27,200	12,338

- 5 to 1 design factor standard
- 7 to 1 design factor available upon request
- Higher capacities available on special request
- Designed to meet or exceed: ASME B30.9 Slings, B30.20 Below-the-Hook Lifting Devices; AWS D14.1 Welding Procedures