

PLAIN TROLLEYS MODEL: PT

These trolleys are designed to suit a wide range of monorails and fabricated beams. They have many applications in the mining, oil & gas, heavy construction and marine industries.

- Strong rugged construction.
- Easily adjusted to any beam width within range.
- Powder coated paint finish.
- Precision ball bearing trolley wheels with machined tread for smooth operation.
- Conforms to ASME/ANSI B30 standards where applicable.



Model	Capacity	Adjustable Beam Width (inches)	Dimensions (inches)				Minimum Radius Curve (ft)	Weight (lbs.)
			A	B	C	H		
TUF-PT.5	0.5 ton	* Call for specifications*						
TUF-PT10	1 ton	2.52 - 8.27	12.52	10.24	9.41	5.31	3.28	31
TUF-PT20	2 ton	3.46 - 8.27	13.19	11.81	11.26	6.34	3.61	46
TUF-PT30	3 ton	4.02 - 8.27	14.31	13.58	13.23	7.4	4.26	88
TUF-PT50	5 ton	4.49 - 8.27	15.07	15.55	15.47	8.66	4.59	113
TUF-PT100	10 ton	6.5 - 8.27	16.13	17.91	19.69	11.02	5.58	198
TUF-PT200	20 ton	6.5 - 8.27	19.5	25.48	24.5	12.4	15	502

